



Lexington Tech International Linesheet

LTI Products	Manufacturers represented / vendor partners	Description / Capacity
Actuator: Electric	BY Controls	<i>Rotary type electric and Linear type electric actuators. Can also supply with valve positioner, limit switch, solenoid valves, I/P transducers, manual handwheels, etc.</i>
Actuator: Hydraulic	BY Controls	<i>Rack and Pinion type hydraulic</i>
Actuator: Pneumatic	BY Controls	<i>Reverse type and direct type pneumatic diagram actuators</i>
Adapter, Crossover	Sandong Metal Industry Co., Ltd.	<i>Union Thread x Union Nut, Union Thread x Union Thread, Union Nut x Union Nut. Sizes can be changed for customer's requirements.</i>
Air Compressor	Ingersoll Rand	<i>Air Compressors as well as Tools, Air Motors, Starters, parts and accessories</i>
Battery	SAFT/HV	<i>The world's leading designer and manufacturer of advanced-technology batteries for industry, Saft products are widely acknowledged to be reliable, safe, cost-efficient, long-life and respectful of the environment. Nikckel-based batteries, primary lithium and new-generation lithium-based batteries and battery systems</i>
Blower	Yujin Engineering & Mfg. Co., Ltd.	<i>Centrifugal Fans & Blowers (Air Volume 20-10,000 m3/min, 1000-8000 mmAG) Axial Flow Fans (Air volume 50-50,000 m3/min, 0-450 mmAG)</i>
Blower: Centrifugal	Gardner Denver	<i>Sonic centrifugal blowers feature an automatic belt tensioning system and are compatible with both NEMA & IEC motors. Find the right fit for your unique application with blower enclosures that reduce noise and protect drive & belts, HEPA or ULPA filters, durable aluminum or stainless steel Sonic XE Air Knives with multiple inlet configuration options, and air wipes for a 360 degree blow off</i>
Blower: Positive Displacement	Gardner Denver	<i>Sutorbilt, Mobile Blowers, CycloBlower, DuroFlow, HeliFlow, TriFlow, IQ Blower Package, PD Blower Lubricants</i>
Boiler: Industrial, Utility	Macchi	<i>Industrial Boiler, Heat Recovery Boiler, Utility Boiler, Steam Generators, Waste to Energy Boilers</i>
Boiler: Industrial, Co-Gen Power, Auxiliary	Daekyung Engineering	<i>Industrial, Co-Gen Power, Auxiliary Boilers, Preheaters Head Office & Fabrication Shop No.1 (5km from Ulsan Port): Total Area : 13,000 m², Fabrication Shop No.2 Total Area : 6,000 m²</i>
Brakes	Kobelt Manufacturing	<i>Air-Applied Brakes, Spring-Applied Brakes, Hydraulic-Applied Brakes, Discs, Accessories</i>
Bushing	Elscom, Inc.	<i>Power contact, Earthing contact, Disconnecter, Bus Bar Holder, Power Distribution Rail, MCC Auto Shutter, Shutter key, MCC Bucket roller, Hour Meter, H/V Bushing, Insulator, Cable Way Bolt Cap, Hole Blind Packing, L/V and H/V Cable Holder, Name Plate Rivet, Hinge for H/V SWGR, Cable Grommet, Duct Piec, Auxiliary Switch, Push Button Protection Cover</i>
Cable: Extra-high Voltage	LS Cable & System, Ltd.	<i>XLPE Insulation cables, OF cables, Superconducting cables</i>
Cable: High Voltage	LS Cable & System, Ltd.	<i>Copper or aluminum round compacted circular or segmental compacted circular according to the international specifications IEC 60228 or any customer's specification.</i>
Cable: Low and Medium Voltage, Power Distribution	Daewon Cable Co., Ltd.	<i>Cross-Linked Polyethylene insulated power cable, armoured cable, water blocking cables</i>
	LS Cable & System, Ltd.	<i>Fire-resistant cables, Eco-friendly cables, Fireproof cables</i>

For inquiries, please contact us today at: info@lexintec.com

Tel 832-300-1100 | Fax 832-300-1104

LTI Products	Manufacturers represented / vendor partners	Description / Capacity
Cable: Accessories	Elscom, Inc.	<i>Power contact, Earthing contact, Disconnecter, Bus Bar Holder, Power Distribution Rail, MCC Auto Shutter, Shutter key, MCC Bucket roller, Hour Meter, H/V Bushing, Insulator, Cable Way Bolt Cap, Hole Blind Packing, L/V and H/V Cable Holder, Name Plate Rivet, Hinge for H/V SWGR, Cable Grommet, Duct Piec, Auxiliary Switch, Push Button Protection Cover</i>
Cable: Bus Duct	LS Cable & System, Ltd.	
Cable: Control/ Instrument	LS Cable & System, Ltd.	<i>Unshielded cables, Copper shielded cables, Aluminum shielded cables</i>
Cable: Industrial Specialty	LS Cable & System, Ltd.	<i>Cables for Submarine, Vessels, Navy Vessels, Railway, Wind Power, and Nuclear applications</i>
Cable: Insulation	LS Cable & System, Ltd.	<i>Cables shielded with PVC and XLPE (cross-link polyethylene) insulation provide superior heat resistance (90 °C), are smoke and fire resistant, and eco-friendly according to the environment and application. Such cables are suitable for public facilities such as high buildings, hospitals, underground markets, airports and subways due to their high fire-resistance and lack of smoke and toxic gas emission in case of fire.</i>
Cable: Optical Fiber	Daewon Cable Co., Ltd.	<i>Single mode or Multi-mode (graded index fiber), connectors</i>
Cementing & Steel Hose Loop	Sandong Metal Industry Co., Ltd.	<i>Cementing Steel Hose Loops are available for 2" and 3" of nominal pipe sizes. Suitable for Cementing lines, Water Lines, Well Testing lines, etc. Cementing Steel Hose Loops are available for Standard and H2S Service. Long Radius Cementing Steel Hose Loops are suitable for pressures up to 15,000psi, Short Radius Cementing Steel Hose Loops are suitable for pressures up to 6,000psi, Styles of SMI Cementing Steel Hose Loops are customized.</i>
Clamps	PLIDCO	<i>High pressure pipeline repair and maintenance fittings from 10,000 psi and temperatures from -250° F to 1100° F. An inventory of standard products in API pipe size, 1-1/2" through 48" and pressures up to 2000 psi are stocked</i>
Coalescing Media Pack	Donghae Industry Co., Ltd.	<i>The Pack is a key part of the Oil-Water Separator. It has been designed in the form of several egg container shaped trays with holes for the oil at the crests of the cups and holes for the sludge in the valleys of the cups. This provides several thousand partitions having the effect of shortening sedimentation for floating sludge in the oil several hundred times over.</i>
Column & Tower	Ilung Corporation	<i>Maximum Size 15mX 140m, 1,500 Tons/Set, Pressure 700Kg/Cm2 (9940 PSI), Thickness 300mm (12") 18000 Tons/Year. Shop Area: 1,457,000 sq. ft. Max Size: H30m x W50m x L100m, 2000 Ton/Set, 12,000 Tons/year. Materials (Origin: USA, Korea, Japan, Europe), HIC, Killed C/S Non-ferrous: Copper Alloy, Titanium Alloy, Nickel Alloy (Monel, Inconel), Clad Steel: 304/304L, 410SS, Monel, Inconel, Ti, Low Alloy (CR-Mo, Cr-Mo-V)</i>
Column, Tower Depentanizer	Daekyung Engineering	<i>Max Capacities-Diameter 5,000mm, Length 80,000mm, Thickness 150 mm, Weight 250 ton</i>
Compressor	Gardner Denver/Pinnacle	<i>Oil-Free Rotary, Oil-Lubricated Rotary Screw, Reciprocating, Centrifugal Air and Natural Gas Compressors. Air Treatment and Compressed air accessories</i>
Connector & Plug	Elscom, Inc.	<i>Electric Systems & Components, Explosion proof</i>
Contact	Elscom, Inc.	<i>Power contact, Earthing contact, Disconnecter, Bus Bar Holder, Power Distribution Rail, MCC Auto Shutter, Shutter key, MCC Bucket roller, Hour Meter, H/V Bushing, Insulator, Cable Way Bolt Cap, Hole Blind Packing, L/V and H/V Cable Holder, Name Plate Rivet, Hinge for H/V SWGR, Cable Grommet, Duct Piec, Auxiliary Switch, Push Button Protection Cover</i>
Control Station	Elscom, Inc.	<i>Electric Systems & Components, Explosion proof</i>
Control System	Kobelt Manufacturing	<i>Electronic (control heads, microprocessors, actuators, panels, other), Pneumatic (actuators, valves, control heads), and Mechanical (control heads, cables, accessories) controls</i>

For inquiries, please contact us today at: info@lexintec.com

Tel 832-300-1100 | Fax 832-300-1104

LTI Products	Manufacturers represented / vendor partners	Description / Capacity
Distribution Board	Elscom, Inc.	<i>Electric Systems & Components, Explosion proof</i>
Dredges	Ellicott Dredges, LLC.	<i>Ellicott® Dredges, one of the oldest and most successful dredging equipment companies in the world, has been supplying dredging equipment to governments, municipalities, contractors, sand and gravel operators, port authorities, and marina operators for over 125 years. Portable cutterhead, swinging ladder, large cutterhead, custom, pump barges, booster pump assemblies, and parts</i>
Drives	Kobelt Manufacturing	<i>"Get-Home" Drives, DC Alternators, Generators</i>
Dryer	Gardner Denver	<i>Refrigerated and regenerative air dryers, can offer custom engineering capabilities for your blower, exhauster, pressurized air, vacuum, and all gas handling needs.</i>
Electrical Parts	Various	<i>Terminations, joints, bus ducts, clips, bare conductors, etc</i>
Electrode Holder	SWSI	
Element	Pinnacle	<i>Accordion Hose, Air Filter Element, Air/Oil Separator Box, Air/Oil Separator Element, Air/Oil Separator Kit, By-Pass Oil Filter Element, Felt Star Element, Filter Element, Fuel Filter Element, High Pressure Oil Filter Element, Micro-Top Element, Oil Filter Element, Oil Filter Element - Metal Free, Safety Element</i>
Fan	Yujin Engineering & Mfg. Co., Ltd.	<i>Centrifugal Fans & Blowers (Air Volume 20-10,000 m3/min, 1000-8000 mmAG) Axial Flow Fans (Air volume 50-50,000 m3/min, 0-450 mmAG)</i>
Filter	Pinnacle	<i>Air/Oil Separator Box, Air/Oil Separator Kit, Cabin Filter, Candle, Centrifuge Element, Conversion Kit, Cooling Liquid Filter, Cyclone, Damping Filter, Disk, Disk Strainer Assy., Disk Strainer Filter, Disk Strainer Insert, Dust Collector, EDM Filter, EDM Handle, Ejector, Ejector Adapter, Elbow Assy., Endcap Assy., Felt Star Insert, Filling Strainer, Filter Head Assy., Finned Primary Filter, Flange Assy., Fuel Filter, Fuel/Water-Separator, Gap Filter, High Pressure Filter, Housing, HP Spin-on Fuel Filter, Hydraulic Spin-on Filter, Impeller, Inline Fuel Filter, Insert, Micro-Top Filter, Micro-Top Oil Filter, Micro-Top Suction Filter, NLG-Pico, Oil Container Assy., Oil Filter, Oil Separator, Oil Separator Wire Mesh, Oil Water Separator Spin-on, Oil-Bath Air Cleaner, Piclon, Pico Air Cleaner, Pico Air Filter, Pico-E, Pico-E Air Cleaner, Picolino, Plate Gap Filter, Plate Gap Filter Stainless Steel, Plate Gap Insert, Plug, Plug Assy., Plug Cover, Plug Screw, Pocket Strainer Assy., Pocket Strainer Insert, Pot Assy., Seals for Automatic Filter, Seals for Tap or Ballcock, Secondary Spin-on Oil Filter, Silencer Filter, Silencer Pipe Assy., Slotted Tube Insert, Spin-on Coolant Filter, Spin-on Fuel Filter, Spin-on Oil, Filter, Spiral Hose, Star-Shaped Strainer Assy., Star-Shaped Strainer Filter, Star-Shaped Strainer Insert, Strainer Basket, Strainer Insert, Strainer Tube Assy., Strainer Tube Filter, Strainer Tube Insert, Strap Assy., Ventilation Filter, Wet Air Cleaner, Wet Air Insert, Wire Gap Filter, Wire Gap Insert, Wire Gap Tube, Wire Gap Tube Filter, Wire Gap Tube Filter Stainless Steel, Wire Gap Tube Insert</i>
Filtration and separation system	Donghae Industry Co., Ltd.	<i>Oily water separator, oil water separator, oil removal, underground oil water separator</i>
Finned Tube	Heat Transfer Tubular Products, LLC.	<i>Finned Tubes, Custom U-Bends, Custom Turbulator used in heat exchangers, condenser, boilers, feed-water heaters and economizers.</i>

For inquiries, please contact us today at: info@lexintec.com

Tel 832-300-1100 | Fax 832-300-1104

LTI Products	Manufacturers represented / vendor partners	Description / Capacity
Finned Tube	KHEI	<p><u>Extruded:</u> This is an integrated fin tube which is fabricated by extruding fins from the aluminum bloom covered over the base tube. This is best suited for the highly corrosive environment. The applicable temperature is up to 545 F degree (285 C degree)</p> <p><u>Embedded'G':</u> The strip is embedded under the tension in a groove of the base tube. The impact of a differential expansion coefficient is minimal so that the G-type fin tube is applicable to high temperature up to 150 F degree (400 C degree)</p> <p><u>'L' Footed:</u> The strip is wound under the tension around a base tube. The contact between the fin and the base tube by 'L' foot shape so that the contacting surface is increased. The applicable temperature is up to 270 F degree (130 C degree)</p> <p><u>'LL', Double 'L':</u> The strip is wound under the tension around a base tube. However, unlike the L-type the foot is overlapped to the previous foot because of the overlapped foot. The applicable temperature is up to 330 F degree (165 C degree)</p>
Fittings: Elbow, Swage, Studded Cross/ Tee	Sandong Metal Industry Co., Ltd.	Fittings are available for 2" and 3" nominal pipe sizes. For the 4" nominal pipe size items are customized. All Fittings are available for Standard and H2S service. Wide range of fittings from Elbows to Swages with integral 1502 union end, Standard CWP 15,000psi/TP 22,500psi and H2S service CWP 10,000psi/TP 15,000psi
Flange	Sandong Metal Industry Co., Ltd.	API 6A-TYPE 6B FLANGES FOR 2,000psi, API 6A-TYPE 6B FLANGES FOR 3,000psi, API 6A-TYPE 6B FLANGES FOR 5,000psi, API 6A-TYPE 6BX Integral Flanges, API 6A-TYPE 6BX Welding Neck Flanges, API 6A TYPE 6BX Blind and Test Flanges
Frac Adapter, Goat Head	Sandong Metal Industry Co., Ltd.	5 1/8" CWP 10,000psi, Tested at 15,000psi with Four 4" 1002 Female Inlets, Material : AISI 4135, Hard faced on critical area 7 1/16" CWP 10,000psi Tested at 15,000psi with Four 4" 1002 Female Inlets, Material : AISI 4135, Hard faced on critical area
Gas Equipment	SWSI	Outfits, Regulators, Handles, Welding Nozzles, Heating Tips, Cutting Tips and Torches
Gaskets: Standard, Insulation and Hi-flex	Kukil Inntot Co., Ltd.	Monthly production capacity: Metal Gasket 75,000 Ea. SPW Gaskets 200,000 Ea., DJAF 5,000, Sheet Gaskets 60,000, Mold Packing 13,000, Coupling 10,000. SPW Gaskets Auto Machine, Auto Outer Ring Assy Machine, Laser Cutting M/C, sheet Auto Cutting M/C etc.
Generator: Electrical	Kobelt Manufacturing	"Get-Home" Drives, DC Alternators, Generators. Fluid power electrical generator drive system that delivers constant voltage regardless of engine speed.
Generator: Nitrogen	Great Lakes Air/Pinnacle	Nitrogen generators. Nitrogen is used to maintain pressure in oil and gas reservoirs; to blanket storage tanks and product loading/unloading; to purge pipelines; and to strip volatile organic compounds (VOCs) from waste streams. Controlling VOC emissions helps refiners comply with U.S. Clean Air Act requirements.
Ground Clamp	SWSI	Ground clamps and Rotary ground clamps
Hammer Union	Sandong Metal Industry Co., Ltd.	<p>SMI Hammer unions are manufactured by steel forgings using appropriate materials to specific pressure ratings. SMI Hammer unions are available in a choice of end connections. API line pipe threads are standard. Butt Weld End is available. Customer needs to specify schedule of pipe while ordering. H2S service is available and all H2S service parts of SMI unions conform to the latest NACE specifications.</p> <p>All SMI Hammer union components can be interchangeable with WECO on the same size and figure. All SMI Hammer union nuts have three hammer lugs. SMI Hammer unions for low-pressure services (Fig 100 - Fig 200) feature a primary metal-to-metal seal. This metal-to-metal seal remains leak-proof even one surface is slightly pitted or misaligned. SMI Hammer unions for Medium-pressure services (Fig 400 - Fig 600) is designed supplement the metal-to-metal seal with a resilient O-ring in the male sub. The replaceable O-ring extends useful life for union and protects the metal-to-metal seal against corrosion.</p>
Handwheel	BY Controls	Reverse type and direct type pneumatic diagram actuators, Rack and Pinion type Hydraulic, Rotary type electric and Linear type electric actuators. Can also supply electric motor driven type, with valve positioner, limit switch, solenoid valves, I/P transducers, manual handwheels, etc.

For inquiries, please contact us today at: info@lexintec.com

Tel 832-300-1100 | Fax 832-300-1104

LTI Products	Manufacturers represented / vendor partners	Description / Capacity
Heat Exchanger: Air Cooled	KHEI	<i>An Air Cooled Heat Exchanger is a heat transfer device for rejecting heat from a hot fluid directly to fan-blowing ambient air. The obvious advantage of an Air Cooled Heat Exchanger is that it does not require water, which means that plants requiring large cooling capacities need not be located near a supply of cooling water. An Air Cooled Heat Exchanger may be as small as an automobile radiator or large enough to reject the heat of turbine exhaust steam condensation. An Air Cooled Heat Exchanger may consists of the following components: One or more tube bundles, Air moving parts such as a fan, blower, or stack, Fan driver such as Electric Motor, Plenum between air moving parts and the tube bundle, Steel structure to support and allow space for Inlet ambient air to enter, Optional header and Motor maintenance walkways with ladders to grade, Optional louvers for process outlet temperature control, Optional recirculation ducts and chambers for protection against freezing or solidification of high pour point fluids in cold weather, Optional variable pitch fan hub for temperature control and power savings. Temperature Control by Fan, Louver, Steam coil, or hot air recirculation system</i>
Heat Exchanger: Shell & Tube	Daekyung Engineering	<i>Waste Heat Boiler, VG Trim Cooler, Ethylene Turbine Condenser, Dilution Steam Super Heater, CG Compressor 1st Stage Cooler, Flashed feed/HVGO PA & Product Exchanger, Polishing Reactor Feed/Effluent Exchanger, Methanol Loop Cold Interchanger Max Capacities–Diameter 6,000mm, Length 50,000mm, Thickness 150 mm, Weight 250 ton</i>
	Ilsung Corporation	<i>Maximum Size 15mX 140m, 1,500 Tons/Set, Pressure 700Kg/Cm2 (9940 PSI), Thickness 300mm (12") 18000 Tons/Year. Shop Area: 1,457,000 sq. ft. Max Size: H30m x W50m xL100m, 2000 Ton/Set, 12,000 Tons/year. Materials (Origin: USA, Korea, Japan, Europe), HIC, Killed C/S Non-ferrous: Copper Alloy, Titanium Alloy, Nickel Alloy (Monel, Inconel), Clad Steel: 304/304L, 410SS, Monel, Inconel, Ti, Low Alloy (CR-Mo, Cr-Mo-V)</i>
Heat Exchanger: Tubular	KHEI	<i>Engineering capabilities to design both HP and LP heaters. All heaters are designed in aid of computer to meet specific requirements of each end user. KHE is equipped with heavy duty equipment necessary to fabricate large size HP heaters. Design Pressure Up to 250 kg / cm2 G, Design Temperature Up to 450 C degree, Weight Up to 60 ton / bundle, Size 3,000 mm O.D.x 12,000 mm L, Material: Carbon, Stainless Steel, High Alloy etc.</i>
Hose & Lances	Gardner Denver/Pinnacle Industries, Ltd.	<i>Flex Lances, Rigid Lances, Rubber Waterblast Hoses, Thermoplastic Hoses</i>
Hydraulics	Kobelt Manufacturing/Don Harmon	<i>Custom hydraulic power units for all types of systems, can be manufactured in multiple sizes with different power levels, depending on what is required to power the system.</i>
Instrumentation & Control	BY Controls	<i>Valve remote control system (VRCS) is a convenient system which make it possible to operate the valves installed in the cargo and/or ballast tanks from the remote wheelhouse using only push buttons on the central control console.</i>
	Elscom, Inc.	<i>Electric Systems & Components, Explosion proof control stations, distribution boards, Connector & Plug, Junction box, meters</i>
Insulator	Elscom, Inc.	<i>Power contact, Earthing contact, Disconnecter, Bus Bar Holder, Power Distribution Rail, MCC Auto Shutter, Shutter key, MCC Bucket roller, Hour Meter, H/V Bushing, Insulator, Cable Way Bolt Cap, Hole Blind Packing, L/V and H/V Cable Holder, Name Plate Rivet, Hinge for H/V SWGR, Cable Grommet, Duct Piec, Auxiliary Switch, Push Button Protection Cover</i>
Junction Box	Elscom, Inc.	<i>Electric Systems & Components, Explosion proof</i>
Limit Switch	BY Controls	<i>Reverse type and direct type pneumatic diagram actuators, Rack and Pinion type Hydraulic , Rotary type electric and Linear type electric actuators. Can also supply electric motor driven type, with valve positioner, limit switch, solenoid valves, I/P transducers, manual handwheels, etc.</i>

For inquiries, please contact us today at: info@lexintec.com

Tel 832-300-1100 | Fax 832-300-1104

LTI Products	Manufacturers represented / vendor partners	Description / Capacity
Manifold: Cement, Flowback, Choke, Well Testing	Sandong Metal Industry Co., Ltd.	<i>SMI Manifolds are designed and manufactured to meet customer's requirements such as 4, 7, 8 or 9 Valve Manifold. SMI offer a wide range of hammer union ended equipments: Plug Valves, Adjustable Chokes, Positive Chokes, Forged Tees, Crosses, Laterals, Crossovers, API 6A flanged end equipments, etc. Pressure Tested Assembly, Individually Pressure Tested Fittings and Valves, Full Material Traceability, Standard and HS service, API 6A PSL 1,2,3, or 4, All API 6A Material class available, Temperature Rating P to U, Third Party Approval and Vertificates on Design and Manufacturing available, Skid Mounted if required</i>
Meter	Elscom, Inc.	<i>Electric Systems & Components, Explosion proof</i>
Modular Equipment: Onshore Process Module, Offshore Platform & FPSO relevant modules.	Ilsung Corporation	<i>Maximum Size 15mX 140m, 1,500 Tons/Set, Pressure 700Kg/Cm2 (9940 PSI), Thickness 300mm (12") 18000 Tons/Year. Shop Area: 1,457,000 sq. ft. Max Size: H30m x W50m xL100m, 2000 Ton/Set, 12,000 Tons/year. Materials (Origin: USA, Korea, Japan, Europe), HIC, Killed C/S Non-ferrous: Copper Alloy, Titanium Alloy, Nickel Alloy (Monel, Inconel), Clad Steel: 304/304L, 410SS, Monel, Inconel, Ti, Low Alloy (CR-Mo, Cr-Mo-V)</i>
Motor	Pedrollo S.p.A.	<i>Electric motors and pump controls. Surface pumps from 0.5 HP to 100 HP, submersible line4" and 6" from 0.50 HP to 40 HP Sump, effluent and sewage pumps from 0.33 HP to 4.0 HP</i>
Nozzle	Gardner Denver	<i>10/15K Tube Cleaning Nozzles, 40K Tube Cleaning Nozzles, Pineapple Line Moles, 20K Tube Cleaning Nozzles</i>
Oil Skimmer	Donghae Industry Co., Ltd.	<i>Pipe oil skimmer, scraping oil skimmer, floating oil skimmer, belt oil skimmer</i>
Oil Spill Containment Boom	Enviro-USA	<i>40 years of industry experience, applications for refineries, ports, marinas, marine construction and dredging projects</i>
Packing	Kukil Inntot Co., Ltd.	<i>Monthly production capacity: Metal Gasket 75,000 Ea. SPW Gaskets200,000 Ea., DJAF 5,000, Sheet Gaskets 60,000, Mold Packing 13,000, Coupling 10,000. SPW Gaskets Auto Machine, Auto Outer Ring Assy Machine, Laser Cutting M/C, sheet Auto Cutting M/C etc.</i>
Pipe	Dong Yang Steel Pipe Co., Ltd.,	<i>Polyethylene/FBE Coated Steel Pip, Polyurea coated steel pipe for water works, steel pipe for oil & gas transport, coated and wrapped pipes for water services, steel pipe piles. Longitudinal and Spiral Submerged Arc Welded Steel Pipes in diameter range from 400mm to 3,200mm, for the purpose of Water Transportation, Oil & Gas Transportation, Piling and General Structural Use. Also equipped with internal and external coating facilities for Liquid Epoxy, Fusion Bonded Epoxy, Coal-tar Enamel, Asphalt and Extrusion 3 Layer Polyethylene Coating</i>
Positioner	BY Controls	<i>Reverse type and direct type pneumatic diagram actuators, Rack and Pinion type Hydraulic , Rotary type electric and Linear type electric actuators. Can also supply electric motor driven type, with valve positioner, limit switch, solenoid valves, I/P transducers, manual handwheels, etc.</i>
Power Distribution Rail	Elscom, Inc.	<i>Power contact, Earthing contact, Disconnecter, Bus Bar Holder, Power Distribution Rail, MCC Auto Shutter, Shutter key, MCC Bucket roller, Hour Meter, H/V Bushing, Insulator, Cable Way Bolt Cap, Hole Blind Packing, L/V and H/V Cable Holder, Name Plate Rivet, Hinge for H/V SWGR, Cable Grommet, Duct Piec, Auxiliary Switch, Push Button Protection Cover</i>

For inquiries, please contact us today at: info@lexintec.com

Tel 832-300-1100 | Fax 832-300-1104

LTI Products	Manufacturers represented / vendor partners	Description / Capacity
Power Plant Equipment: Surface Condenser, HP Feedwater, Heater, Steam Drum, Deaerator, etc.	Ilsung Corporation	<p><i>Maximum Size 15mX 140m, 1,500 Tons/Set, Pressure 700Kg/Cm2 (9940 PSI), Thickness 300mm (12") 18000 Tons/Year. Shop Area: 1,457,000 sq. ft.</i></p> <p><i>Max Size: H30m x W50m xL100m, 2000 Ton/Set, 12,000 Tons/year.</i></p> <p><i>Materials (Origin: USA, Korea, Japan, Europe), HIC, Killed C/S Non-ferrous: Copper Alloy, Titanium Alloy, Nickel Alloy (Monel, Inconel), Clad Steel: 304/304L, 410SS, Monel, Inconel, Ti, Low Alloy (CR-Mo, Cr-Mo-V)</i></p>
Pressure Vessel	Daekyung Engineering	<p><i>Propane Storage Bullet, Evaporating Crystallizer, Cold Separator</i></p> <p><i>Max Capacities–Diameter 6,000mm, Length 60,000mm, Thickness 180 mm, Weight 250 ton</i></p>
	Ilsung Corporation	<p><i>Maximum Size 15mX 140m, 1,500 Tons/Set, Pressure 700Kg/Cm2 (9940 PSI), Thickness 300mm (12") 18000 Tons/Year. Shop Area: 1,457,000 sq. ft.</i></p> <p><i>Max Size: H30m x W50m xL100m, 2000 Ton/Set, 12,000 Tons/year.</i></p> <p><i>Materials (Origin: USA, Korea, Japan, Europe), HIC, Killed C/S Non-ferrous: Copper Alloy, Titanium Alloy, Nickel Alloy (Monel, Inconel), Clad Steel: 304/304L, 410SS, Monel, Inconel, Ti, Low Alloy (CR-Mo, Cr-Mo-V)</i></p>
Pump: Centrifugal	Gardner Denver/Pinnacle Industries, Ltd.	<p>From charging reciprocating pumps, cement pumps, triplex and well-service pumps to industrial applications, Gardner Denver Pumps' centrifugal pumps are engineered for severe-duty applications. Many of our centrifugal pumps are available in a variety of packing, wear-plate and shaft options to customize the pump to your application. Gardner Denver centrifugal pumps are available a variety of sizes, from the compact 4X5 pump to the industrial-sized 10X12 pump. Our centrifugal pumps are manufactured to outlast heavy duty applications. Check out all of our centrifugal pumps to learn which of our products is best-suited to your needs.</p>
Pump: Diaphragm	Ingersoll Rand	<p>Air operated diaphragm pumps can easily pump from clean, light viscosity fluids to corrosive, abrasive medium viscosity fluids and can transfer large particles without damage. Due to their pneumatic motor, they could be used in potentially explosive areas. Most of the ARO® diaphragm pumps are ATEX certified (CE Ex11 2GD X). These pumps offer the ability to vary the flow outlet and discharge pressure as slow as 0.26 gallons (1liter) per minute up to 275 gallons (1041 liter) per minute for our larger sizes and adjust fluid pressure up to 125 p.si. (8.6 bar), by using just an air filter / regulator and a needle valve</p>
Pump: Water	Pedrollo S.p.A.	<p><i>Water pumps, electric motors and pump controls. Surface pumps from 0.5 HP to 100 HP, submersible line4" and 6" from 0.50 HP to 40 HP Sump, effluent and sewage pumps from 0.33 HP to 4.0 HP</i></p>
Pumps	Deep Blue Pump	<p>Various petro-chemical pumps, chemical pumps, and water pumps. Flow capacity up to 20,000m3/hr, head up to 3500m, rotor speed up to 22700r/min and temperature range from -100 up to 450 degree Celsius, impeller diameter up to 1m, suction diameter up to 1,2m and suction pressure up to 8 MPa. Custom manufacturer</p>
	Gardner Denver	<p>Drilling Pumps, Mud Pumps, Stimulation & Fracturing Pumps, Well-Servicing</p>
Pup Joint	Sandong Metal Industry Co., Ltd.	<p><i>SMI Pup Joints are available for 2" and 3" of nominal pipe sizes for CWP 15,000psi</i></p> <p><i>4" of nominal pipe size available upon customer's request</i></p> <p><i>15,000psi for Standard Service, 10,000psi for H2S Service</i></p>
Reactor	Ilsung Corporation	<p><i>Maximum Size 15mX 140m, 1,500 Tons/Set, Pressure 700Kg/Cm2 (9940 PSI), Thickness 300mm (12") 18000 Tons/Year. Shop Area: 1,457,000 sq. ft.</i></p> <p><i>Max Size: H30m x W50m xL100m, 2000 Ton/Set, 12,000 Tons/year.</i></p> <p><i>Materials (Origin: USA, Korea, Japan, Europe), HIC, Killed C/S Non-ferrous: Copper Alloy, Titanium Alloy, Nickel Alloy (Monel, Inconel), Clad Steel: 304/304L, 410SS, Monel, Inconel, Ti, Low Alloy (CR-Mo, Cr-Mo-V)</i></p>

For inquiries, please contact us today at: info@lexintec.com

Tel 832-300-1100 | Fax 832-300-1104

LTI Products	Manufacturers represented / vendor partners	Description / Capacity
Reactor	Daekyung Engineering	Reactor with Agitator, Dilution Steam Super Heater, Batch Still Reactor Max Capacities–Diameter 6,000mm, Length 60,000mm, Thickness 180 mm, Weight 250 ton
Safety equipment	SWSI	
Seal	Kukil Inntot Co., Ltd.	Monthly production capacity: Metal Gasket 75,000 Ea. SPW Gaskets 200,000 Ea., DJAF 5,000, Sheet Gaskets 60,000, Mold Packing 13,000, Coupling 10,000. SPW Gaskets Auto Machine, Auto Outer Ring Assy Machine, Laser Cutting M/C, sheet Auto Cutting M/C etc.
Stabilizer	Kobelt Manufacturing	Keypower digital roll fin stabilizers are solid and durable, with an innovative design and rugged construction that provides near neutral buoyancy and low maintenance.
Steam Generator	Daekyung Engineering	Head Office & Fabrication Shop (5km from Ulsan Port): Total Area : 13,000 m ² Fabrication Shop No.2 Total Area : 6,000 m ²
Steering	Kobelt Manufacturing	Hydraulic Steering Systems, Electronic Steering Systems, Accu-Steer Hydraulic Actuators, Steering Controls, Helm Pumps, Cylinders, Tiller Arms, Steering Valves, Other Steering Parts
Storage Tank	Daekyung Engineering	Head Office & Fabrication Shops 19,000 m ²
Stormwater treatment system	Donghae Industry Co., Ltd.	The DH Stormwater treatment system utilizes no moving parts with four different chambers capturing and storing fine particles and other pollutants of concern. DH units capture fine sands and solids and are capable of removing more than 80% of annual total suspended solids from storm water. •Capture and retain 100% of floatable and neutrally buoyancy debris 2.4mm •Efficiency remove solid down to 100µm •Ease of Cleaning EPS-Pack™ Plates •Cross flow Processing •Self-cleaning screen •Hybrid Solutions •Water velocities within the treatment chamber continually shear debris off and keep screen clean
Switch Gear	Elscom, Inc.	Power contact, Earthing contact, Disconnecter, Bus Bar Holder, Power Distribution Rail, MCC Auto Shutter, Shutter key, MCC Bucket roller, Hour Meter, H/V Bushing, Insulator, Cable Way Bolt Cap, Hole Blind Packing, L/V and H/V Cable Holder, Name Plate Rivet, Hinge for H/V SWGR, Cable Grommet, Duct Piec, Auxiliary Switch, Push Button Protection Cover
Swivel Joint	Sandong Metal Industry Co., Ltd.	Size: 2"~3", long and short radii End Type: MxM. MxF Service : Standard (15,000psi), H2S(10,000psi)
Thruster	Kobelt Manufacturing	Hydraulic Thrusters, Electric Thrusters
Transducer	BY Controls	Reverse type and direct type pneumatic diagram actuators, Rack and Pinion type Hydraulic , Rotary type electric and Linear type electric actuators. Can also supply electric motor driven type, with valve positioner, limit switch, solenoid valves, I/P transducers, manual handwheels, etc.
Tube ferrules	Heat Transfer Tubular Products, LLC.	Custom Ferrules, Custom U-Bends, Custom Turbulator used in heat exchangers, condenser, boilers, feed-water heaters and economizers.
Tubing	Heat Transfer Tubular Products, LLC.	Custom Ferrules, Custom U-Bends, Custom Turbulator used in heat exchangers, condenser, boilers, feed-water heaters and economizers.
Turbidity barrier	Enviro-USA	40 years of industry experience, applications for refineries, ports, marinas, marine construction and dredging projects
Turbulator	Heat Transfer Tubular Products, LLC.	Custom Ferrules, Custom U-Bends, Custom Turbulator used in heat exchangers, condenser, boilers, feed-water heaters and economizers.

For inquiries, please contact us today at: info@lexintec.com

Tel 832-300-1100 | Fax 832-300-1104

LTI Products	Manufacturers represented / vendor partners	Description / Capacity
Vacuum	Gardner Denver	<i>Central Vacuum Systems, Flux Recovery systems, Mobile, Vacuum Compressors, Vacuum Pumps</i>
Valve Positioner	BY Controls	<i>Reverse type and direct type pneumatic diagram actuators, Rack and Pinion type Hydraulic , Rotary type electric and Linear type electric actuators. Can also supply electric motor driven type, with valve positioner, limit switch, solenoid valves, I/P transducers, manual handwheels, etc.</i>
Valves: Ball	Fluitek Orsenigo Valves	<i>Ball Valves, ½"- 60", for special applications and harsh environment, including cryogenic and subsea, high pressure, high temperature ratings, double block & bleed.</i>
	Shilla Valves Corp., Inc.,	<i>Ball Valve (R-Boar, F-Bore) Class150-2500, 1/2-40", Bellow Seal Gate & Globe Valve Class 150-600, 1/2-24"</i>
Valves: Butterfly	Tiger Valves	<i>Resilient Seated Butterfly Valves, 2"-24"</i>
Valves: Check	Shilla Valves Corp., Inc.,	<i>Check (Swing, Non Slam tilting, Dual Plate Class150-2500) 1/2-60"</i>
	Fluitek Orsenigo Valves	<i>Check Valves from 2 to 48". For high pressure and high temp application.</i>
Valves: Choke	Sandong Metal Industry Co., Ltd.	<i>Standard service is used up to 15,000psi and tested at 22,500psi, H2S service is used up to 10,000psi and tested at 15,000psi, Rugged Construction with Forged Alloy Steel Body Reliable Performance at high working pressure, Bottom Entry design, Top Entry design, Easy Maintenance, Valve Parts are Interchangeable with most major designs, Suitable for variety of high pressure applications such as fracturing, cementing, acidizing and etc. Each valve is serialized, MTR and Test Report are available at any time.</i>
Valves: Control	BY Controls	<i>2-way and 3-way types.</i>
Valves: Gate	Shilla Valves Corp., Inc.	<i>Gate (Class 150-2500) 1/2"-60"., Bellow Seal Gate & Globe Valve Class 150-600, 1/2-24"</i>
	Fluitek Orsenigo Valves	<i>Gate Valves from 2 to 48". For high pressure and high temp application.</i>
	Sandong Metal Industry Co., Ltd.	<i>For Wellhead and Christmas Tree Equipment, for Wellhead Surface Safety Valves and Underwater Safety Valves for Offshore Service, Chemical Plant and Petroleum Refinery Piping, Boiler and Pressure Vessel, Quality Standard for Steel Castings for Valve, Sulphide Stress Cracking Resistant Metallic Materials, for Oilfield Equipment</i>
Valves: Globe	Shilla Valves Corp., Inc.,	<i>Globe(Class 150-2500) 1/2-24", Bellow Seal Gate & Globe Valve Class 150-600, 1/2-24"</i>
	Fluitek Orsenigo Valves	<i>Globe Valves from 2 to 48". For high pressure and high temp application.</i>
Valves: Pig	Tiger Valves	<i>Shut-Off Pig Valve with the trunnion blockmounted ball valve reduces both torque and stem loading, while adding longer life. It is bi-directional for use as both launcher and receiver, and can be installed with a by-pass where needed.</i>
Valves: Plug	Sandong Metal Industry Co., Ltd.	

For inquiries, please contact us today at: info@lexintec.com

Tel 832-300-1100 | Fax 832-300-1104

LTI Products	Manufacturers represented / vendor partners	Description / Capacity
Valves: Solenoid	BY Controls	
Valves: Trunnion Ball	Sandong Metal Industry Co., Ltd.	<ul style="list-style-type: none"> ·API 6A Trunnion mounted ball valves made by AISI 4140 ·Lip seals for high pressure sealing ·Metal rings for efficient fire safety
Water Jetting	Gardner Denver	<i>Pump Packages, Bare Shaft Pumps, Pump Replacement Parts, Control Guns, Equipment, Hoses & Lances, Fittings, Accessories, Safety Equipment, Nozzles</i>
Water Management System	Elscom, Inc.	<i>Drinking water treatment, Brackish water reverse osmosis system, Sea water reverse osmosis system unit, multi media filters, activated carbon filters, fiber glass sand filters, general use micro filters, cartridge filters, water softeners, arsenic & nitric acid nitrogen removal device, sterilizer, De-ionizer system</i>
Welding & Cutting Equipment	Harris	<i>Metal working products used in the brazing, soldering, welding, cutting and gas distribution industries</i>
Welding Accessories	Profax	<i>Manual welding accessories and automotive spot welders</i>
Welding Products	Profax	<i>MIG, TIG, Submerged Arc, Plasma, Arc Gouging Torches, and consumables</i>
Welding Tools	Victor/Thermadyne	<i>Oxy-fuel welding and cutting torches and regulators, plasma arc cutting and welding systems, arc welding power supplies, hardfacing and welding alloys, a wide array of manual and semi-automatic arc welding torches, tips and accessories, and high pressure gas control products</i>

For inquiries, please contact us today at: info@lexintec.com

Tel 832-300-1100 | Fax 832-300-1104